

PRODUCT DATA SHEET

DP60 Waterproof Cement Additive

A waterproofing additive for cementitious mixtures

Product Description:

DP60 Waterproof Cement Additive is a primary waterproofing additive for addition to mortars, concrete and plaster. It is an essential addition to aid in waterproofing in the construction of structural, retaining and boundary walls, floors, showers, ponds, swimming pools, reservoirs and water features. **DP60 Waterproof Cement Additive** aids in the prevention of rising, falling and penetrating damp.

Characteristics/Advantages:

- Easy to use
- Chloride free
- Water tight but permeable to vapour

Typical Applications:

DP60 Waterproof Cement Additive is used to provide water resistance and water proofing characteristics to cement/sand renders and mortars for application to:

- Facades
- Floor toppings
- Walls
- Jointing mortars

Mixing – Guideline Proportions:

Building Mortar

DP 60 Waterproof Cement Additive	2 kg box
Portland Cement	50 kg
Building Sand	250 kg

Plaster Render

DP 60 Waterproof Cement Additive	2 kg box
Portland Cement	50 kg
Plaster Sand	250 kg

Floor Topping/ Screed

DP 60 Waterproof Cement Additive	2 kg box
Portland Cement	50 kg
River Sand	200 kg

Product Limitations:

The quality and water proofness of cementitious mixes containing **D 60 Waterproof Cement Additive** can be affected by one or more of the following factors: poorly graded or poor quality of sand, excessive water dosage, excessive cement dosage or a lack of adequate curing of the cementitious product. Overdosing with **DP60 Waterproof Cement Additive** can result in the retardation of initial setting of the cementitious mixture.

Product Data:

Appearance:	Powder
Colour:	Grey
Packaging:	Available in 2kg boxes, 5kg & 10kg Buckets
Storage Conditions:	Store in a dry cool area, between 5 -25°C
Shelf Life:	12 months in original unopened packaging.

Health and Safety Information:



Keep out of reach of children. Do not breathe dust. In case of inadequate ventilation wear respiratory protection. Wear protective gloves/ protective clothing/ eye protection. Wash face, hands and any exposed skin thoroughly after handling. For further health and safety information refer to the product SDS.



Stanton Construction Chemicals Pty (Ltd).
Unit 2A Veni View Park 547 Heritage View Drive
Muldersdrift, South Africa, 1735
Tel: +27 (0) 10 593-4454
Email: www.office.co.za
Website: www.sccsa.co.za



The information, and, in particular, the recommendations relating to the application and end-use of SCC products, are given in good faith based on SCC's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with SCC's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. SCC reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. Users must always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of SCC.