

PRODUCT DATA SHEET

ShutterStrip 124

Mineral Based, Emulsified Mould Release Agent

Product Description:

ShutterStrip 124 is an emulsifiable mould release oil that prevents concrete sticking to either the mould or shuttering form work. It produces a smooth finish on the concrete and keeps the mould or shuttering suitable for re-use. In the neat form it is easily applied by brush, swab or spray, but if in emulsified form, spraying is not advisable.

Typical Uses:

Applied over plywood, timber, fibreglass and metal shutters for a smooth off-shutter concrete finish.

Advantages:

- Contains rust inhibitors which will protect metal shutters from rust and corrosion.
- Provides a smooth off-shutter concrete finish
- Easy application

Application:

- **ShutterStrip 124** can be used neat or as an emulsion on moulds and shuttering made from timber, plywood or metal.
- Application can be by brushing, spraying or swabbing, aiming at a concrete coverage with the thinnest possible film. For the best results a mix of 4 parts water to 1 part oil should be used. If it is to be used in the emulsified form, then the required amount of water must be added to the oil and NOT vice versa.
- Add the water a little at a time with constant vigorous stirring to ensure the production of a thin homogeneous emulsion of the water-in-oil type invert emulsion. On no account must all the water be added at the same time.
- Shutters should be prepared about 2 to 4 hours before the concrete is thrown. It is essential to use emulsions the same day as prepared.

Coverage:

Typical coverage is approximately 300m² per 5 litres.

Physical Characteristics:

Viscosity, cSt @ 40 °C 4,0

Density @ 20 °C, kg/l 0,848

Flash Point, °C, typ. 76



Stanton Construction Chemicals Pty (Ltd).

Unit 2A Veni View Park 547 Heritage View Drive
Muldersdrift, South Africa, 1735

Tel: +27 (0) 10 593-4454

Email: www.office.co.za

Website: www.sccsa.co.za



The information, and, in particular, the recommendations relating to the application and end-use of SCC products, are given in good faith based on SCC's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with SCC's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. SCC reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. Users must always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of SCC